



India's #1 brand to remove moisture from the compressed air

hydint & suzhik controls

(ISO 9001: 2008 Factory Owned Marketing Unit for Compressed Air Filtration, Pneumatics, Manual Valves & Pneumatic / Electrica Actuators)

7th Floor, Marble Arch, Opp: Vanijya Bhavan, Race Course, Vadodara - 390 007, Gujarat, INDIA

Cell # +91 971 298 7360 (MK Saiyed) Email: info@hydint.com Website: www.hydint.com

Range of Products - IC-SS Valves - 01/10/2020

Product Image	Product Description	Size in (MM)	Specifications
	Investment Casting, Stainless Steel, Single Piece Design, Ball Valves		Body : Stainless Steel
		8	Ball : Stainless Steel
		10	Stem : Stainless Steel
		15	Seat & Seal : PTFE
		20	Stem Nut : Stainless Steel
		25	Handle : Stainless Steel
		32	Sleeve : Plastic
		40	Gland Packing : PTFE
		50	End Connection : Screwed, BSP (F)
		100	Working Pressure : 10kg/cm ²
			Size : 8mm (1/4") to 100mm (4")
			Media : Water, Oil, Gas, Air & Steam
	Investment Casting, Stainless Steel, 3 Way, Full Bore, 'L' Port/'T' Port, Ball Valves		Body : Stainless Steel
			Ball : Stainless Steel
			Stem : Stainless Steel
		15	Seat & Seal : PTFE
		20	Stem Nut : Stainless Steel
		25	Handle : Stainless Steel
		32	Sleeve : Plastic
		40	Gland Packing : PTFE
		50	End Connection : Screwed, BSP (F)
			Working Pressure : 10kg/cm ²
			Size : 15mm (1/2") to 50mm (2")
			Media : Water, Oil, Gas, Air & Steam
	Investment Casting, Stainless Steel, Swing Check Valves (Non-Return Valves)		Body : Stainless Steel
		15	Cover : Stainless Steel
		20	Disc with Hinges : Stainless Steel
		25	Gasket : PTFE
		32	Hinge Pin with Plug : Stainless Steel
		40	End Connection : Screwed, BSP (F)
		50	Working Pressure : 10kg/cm ²
			Size : 15mm (1/2") to 50mm (2")
			Media : Water, Oil, Gas, Air & Steam
	Investment Casting, Stainless Steel, "Y" Type Strainers	15	Body : Stainless Steel
		20	Cover : Stainless Steel
		25	Screen : Stainless Steel
		32	End Connection : Screwed, BSP (F)
		40	Working Pressure : 10kg/cm ²
		50	Size : 15mm (1/2") to 50mm (2")
			Media : Water, Oil, Gas, Air & Steam
	Automatic Air Vent Valve		Body : Nickel Plated Brass
			Float : Polypropylenic Resin
		15	'O' Ring : NBR
		20	End Connection : BSP Male Thread
		25	Working Pressure : 10kg/cm ²
			Size : 15mm(1/2")- rest on request
			Temperature Resistance : 110° C

Due to our R&D and the worldwide advancement in technology, we reserve our right to make changes from time to time in technical specifications / dimensions without any prior notice

We are manufacturing "Aira" Manual Valves /Pneumatic Actuators, "Cair" Electrical Actuators, "Airmax" Pneumatic Products & "Hydint" Compressed Air Filtration Products - All enquiries are welcome