



HYDINT & SUZHIK CONTROLS

ISO 9001:2008 Factory's Owned Marketing Unit for Compressed Air Filtration, Pneumatics, Manual Valves & Pneumatical / Electrical Actuators - INDIA'S #1 BRAND FOR REMOVING MOISTURE FROM THE COMPRESSED AIR

[Home](#) [Products \(HYDINT\)](#) [Pneumatic Products](#) [Manual Valves](#)

info@hydint.com +91 971 298 7360 [Log In](#)



"HYDINT" AUTO DRAIN VALVE, IC SS-304, (FOR TIMER BASED ELECTRICAL DRAIN) WITH ADJUSTABLE TIMER & FILTER ARRANGEMENT, 15MM, 10KG / 21KG / 60KG

Model: "ADF-695"

(1) MODEL: "ADF-695-2" - 1/2", Screwed, 10kg/sq.cm.

(1) MODEL: "ADF-695-3" - 1/2", Screwed, 21kg/sq.cm.

(1) MODEL: "ADF-695-4" - 1/2", Screwed, 60kg/sq.cm.

SPECIFICATIONS / DATASHEET / CATALOGUE OF MODEL: "ADF-695"

VALVE BODY	: IC-SS-304
TIMER BODY	: ABS Plastic
CHECK NUT	: Steel Plated
CONNECTION PORT	: 15mm (1/2") Female Screwed (BSP)
DESIGN PRESSURE	: 10, 21 & 60kg/sq.cm.
COIL VOLTAGE	: 230V AC, 50-60Hz (110V & 7-36V AC/DC available on request)
CRITICAL AMBIENT TEMP.	: 20-85degree C
HUMIDITY CONDITION	: Less than 85%
MOUNTING	: Indoor (See our Model: WP-HYD-695 for outdoor IP-65 compliant weatherproof application)
MANUAL OVERRIDE	: Reset
OFF TIME	: 0.5 to 45 Minutes (Adjustable)
ON TIME	: 0.5 to 10 Seconds (Adjustable)
SPARE COIL & TIMER	: Available
WARRANTY	: 1 Year (as per our warranty certificate)
TIMER	: Electrical (Adjustable)
MODEL	: "ADF-695-2" (10kg) "ADF-695-3" (21kg) "ADF-695-4" (60kg)

(Due to our R&D and the worldwide advancement in technology, we reserve our right to make changes from time to time in technical specifications, datasheet, catalogue, dimension and images without any prior notice)

[Download](#)